



<sup>1</sup> $l_1$	<sup>2</sup> $d_1$ Thread			<sup>2</sup> $d_2$ H7 Bore		$d_3$	$d_4$	$h_1$	$h_2$	$h_3$	$h_4$ Stroke	$t$ min.
30	M 3	-	-	-	-	10	13	26,5	4	31	3,5	7
30	M 4	M 5	M 6	B 5	B 6	10	13	26,5	4	31	3,5	9
45	M 4	M 5	M 6	B 5	B 6	10	13	26,5	4	35	3,5	9
63	M 6	M 8	-	B 8	-	13,5	17,5	32,5	6,5	45	4	11
78	M 8	M 10	-	B 8	B 10	16	21	37,5	8	55	4	14

**Specification**

- Handle  
Zinc die casting
- plastic coated  
black, RAL 9005  
textured finish ● SW
- Push button  
Plastic  
black, RAL 9005 ● S  
orange, RAL 2004 ● O  
grey, RAL 7035 ● G
- Threaded insert  
Steel, blackened
- Pin for push button  
Stainless Steel
- ISO-Fundamental Tolerances → Page 1132
- RoHS compliant

**On request**

- Handle in colours of GN 300

**Information**

Adjustable hand levers GN 303 are ideal whenever parts have to be clamped in a confined space or in a particular lever position. The centre insert is connected to the lever via serrations which can easily be disengaged.

The push button is a design element that offers an easy disengagement. Its use is limited to applications where dismantling of the lever for installation is not required.

see also...

- Adjustable hand levers GN 303.1 (insert Stainless Steel) → Page 204

How to order	<sup>1</sup> $l_1$
	<sup>2</sup> $d_1$ ( $d_2$ )
<b>GN303-78-M10-SW-G</b>	<sup>3</sup> Handle colour
	<sup>4</sup> Push button colour