



ROSTFREI
Inox
Stainless
Steel

3 Type
WK Stainless Steel-PTFE /
Stainless Steel
self lubricated

1 d_1 H7	2 d_2 h6	b_1 -0,2	b_2	w Movement angle
5	13	8	6	13°
6	16	9	6,75	13°
8	19	12	9	14°
10	22	14	10,5	13°
12	26	16	12	13°
14	28*	19	13,5	16°
16	32	21	15	15°
18	35	23	16,5	15°
20	40	25	18	14°
22	42	28	20	15°
25	47	31	22	15°
30	55	37	25	17°

DIN ISO 12240-1: Ø 29

Specification

- Pairing
Type WK (self lubricated)
 - Bearing socket
Stainless Steel AISI 316Ti
with PTFE-insert
 - Internal ring
Stainless Steel AISI 420
hardened, ground, polished
- ISO-Fundamental Tolerances → Page 323
- RoHS compliant

Information

Stainless Steel-Ball joints GN 648.9 are similar to DIN ISO 12240-1, series K.

These Stainless Steel-Ball joints are integrated in the Stainless Steel-Ball joint heads GN 648.5 and GN 648.6.

see also...

- *Stainless Steel-Ball joint heads with female thread GN 648.5*
→ Main Catalogue Page 950
- *Stainless Steel-Ball joint heads with threaded bolt GN 648.6*
→ Main Catalogue Page 951

How to order

GN648.9-19-32-WK

1 d_1
2 d_2
3 Type