



EDELSTAHL®
Rostfrei
Inox
Stainless
Steel

1 2 3

d ₁	d ₂	l ₁				l ₂	l ₃ ≈	m	A/F
15	M 6	26	36	46	-	7,6	3,6	5,2	3
15	M 8	20	35	45	58	7,6	2,5	6,8	4
18	M 8	20	35	45	58	9,2	4,2	6,8	4
18	M 10	34	44	57	74	9,2	3,4	8,4	5
21	M 8	20	35	45	58	10	5	6,8	4
21	M 10	34	44	57	74	10	4,3	8,4	5
21	M 12	34	57	74	94	10	3,4	10,8	6
25	M 8	20	35	45	58	10,5	5,5	6,8	4
25	M 10	34	44	57	74	10,5	4,6	8,4	5
25	M 12	34	57	74	94	10,5	3,6	10,8	6
32	M 8	20	35	45	58	11	6	6,8	4
32	M 10	34	44	57	74	11	5	8,4	5
32	M 12	34	57	74	94	11	4,2	10,8	6
40	M 8	20	35	45	58	13	8	6,8	4
40	M 10	34	44	57	74	13	7	8,4	5
40	M 12	34	57	74	94	13	6,2	10,8	6

Specification

- Thrust pad
Plastic (Polyacetal POM)
- temperature resistant up to 80 °C
- matte black
- Grub screw
- Steel **ST**
Tensile strength class 5.8 (500 N/mm²)
blackened finish
- Stainless Steel AISI 303 **NI**
- Hex jam nuts ISO 4032
- Steel
zinc plated, blue passivated finish
- Stainless steel AISI 303
- *Stainless Steel characteristics* → Page 1144
- **RoHS compliant**

4

Information

GN 903 toggle clamp spindle assemblies are an economical choice for use with various toggle clamps that require manual clamping height adjustments on even or uneven surfaces. Toggle screw swivels up to 15° in any direction.

Thrust pad can be easily detached from and reassembled to screw.

see also...

- *Clamp mounts GN 809* → Page 770
(for toggle clamps with solid clamping arm)

Steel-Clamping bolts

1 2 3 4
GN 903-18-M8-35-ST

1	d ₁
2	d ₂
3	l ₁
4	Material

Stainless Steel-Clamping bolts

1 2 3 4
GN 903-21-M12-57-NI

1	d ₁
2	d ₂
3	l ₁
4	Material