


2 Identification No.

2 with Stainless Steel-Clamping screw DIN 912



d ₁ Bore B	b Swivel width	d ₂	d ₃ Clamping thread	d ₄	k	Length l	m	s	t	Clamping lever for d ₃
B 12	25	6,5	M 6	M 6	25	64	29,5	10	12,5	GN 911-M6-22
B 14	25	6,5	M 6	M 6	25	64	29,5	10	12,5	GN 911-M6-22
B 16	25	6,5	M 6	M 6	25	64	29,5	10	12,5	GN 911-M6-22
B 18	25	6,5	M 6	M 6	25	64	29,5	10	12,5	GN 911-M6-22

Specification

- Aluminum
 - plastic coated black, RAL 9005, textured finish ● **SW**
 - blank ○ **BL**
 - blank matt shot-blasted
- Clamping bore mechanically machined
- Socket cap screws DIN 912
Stainless Steel AISI 304
- Hexagon nuts DIN 985
Stainless Steel AISI 304
- Stainless Steel characteristics → Page 1144
- RoHS compliant

Accessory

- Clamping kits GN 911 → Page 1031



Information

The clamping bore of GN 273 swivel clamp connectors is mechanically machined and designed for construction tubes GN 990 or DIN 2391, DIN 2395 and DIN 2462 respectively.

The standard version of the clamping screw is a socket cap screw with hexagonal socket DIN 912. It can be replaced by a clamping kit GN 911 (article code see table of dimensions).

GN 273 swivel clamp connectors can be assembled with swivel clamp connectors GN 271, GN 275 or GN 277 to create swivel clamp connector joints.

see also...

- Construction tubes GN 990 → Page 1027
- Retaining rods / Retaining tubes GN 480.1 → Page XYZ
- Swivel clamp connector joints GN 283 (Connection of GN 273 with GN 275) → Page 1017
- Swivel clamp linear actuator connectors GN 273.1 → Page 1054
- Sensor holders GN 273.4 → Page 1026
- Swivel clamp mountings GN 482 → Page XYZ

How to order

GN 273-B16-2-SW

1	d ₁
2	Identification No.
3	Finish