



ROSTFREI
Inox
Stainless
Steel

| 2 | | | Length l ±0,5 | 3 | | 2 | | | Length l ±0,5 | 3 | |
|------------------------------------|------------|-----------------|--|----------------|----------------|----------------------------------|------|------|--|----------------|----------------|
| d ₁ Diameter D ST | AL | NI | | d ₂ | w ₁ | s ₁ Square V ST | AL | NI | | s ₂ | w ₂ |
| D 10 ±0,1 | D 10 ±0,1 | D 10 ±0,1 | available are all lengths in 1 mm steps max. length 3000 mm | 7 | 1,5 | - | V 10 | - | available are all lengths in 1 mm steps max. length 3000 mm | 7 | 1,5 |
| D 12 ±0,1 | D 12 ±0,1 | D 12 ±0,1 | | 9 | 1,5 | - | V 12 | - | | 9 | 1,5 |
| D 14 ±0,1 | D 14 ±0,1 | D 14 ±0,1 | | 11 | 1,5 | - | V 16 | - | | 13 | 1,5 |
| D 15 ±0,1 | D 15 ±0,1 | D 15 ±0,1 | | 12 | 1,5 | V 20 | V 20 | V 20 | | 16 | 2 |
| D 16 ±0,1 | D 16 ±0,1 | D 16 ±0,1 | | 13 | 1,5 | V 25 | V 25 | V 25 | | 21 | 2 |
| D 18 ±0,1 | D 18 ±0,1 | D 18 ±0,1 | | 15 | 1,5 | V 30 | V 30 | V 30 | | 26 | 2 |
| D 20 ±0,1 | D 20 ±0,1 | D 20 ±0,1 | | 16 | 2 | V 35 | V 35 | - | | 31 | 2 |
| D 25 ±0,1 | D 25 ±0,1 | D 25 ±0,1 | | 21 | 2 | V 40 | V 40 | V 40 | | 34 | 3 |
| D 30 ±0,1 | D 30 ±0,1 | D 30 ±0,1 | | 26 | 2 | V 45 | V 45 | V 45 | | 39 | 3 |
| D 32 ±0,15 | D 32 ±0,15 | D 32 ±0,15 | | 28 | 2 | V 50 | V 50 | V 50 | | 44 | 3 |
| D 35 ±0,15 | D 35 ±0,15 | D 35 ±0,15 | | 31 | 2 | - | - | - | | - | - |
| D 40 ±0,15 | D 40 ±0,15 | D 40 ±0,15 | | 34 | 3 | - | - | - | | - | - |
| D 42 ±0,2 | - | - | | 36 | 3 | - | - | - | | - | - |
| - | - | D 42,4 (1 1/4") | | 37,2 | 2,6 | - | - | - | | - | - |
| D 45 ±0,2 | D 45 ±0,2 | - | | 39 | 3 | - | - | - | | - | - |
| D 48 ±0,2 | D 48 ±0,2 | - | | 42 | 3 | - | - | - | | - | - |
| - | - | D 48,3 (1 1/2") | | 43,1 | 2,6 | - | - | - | | - | - |
| D 50 ±0,2 | D 50 ±0,2 | D 50 ±0,2 | | 44 | 3 | - | - | - | | - | - |
| D 55 ±0,25 | - | - | | 47 | 4 | - | - | - | | - | - |
| D 60 ±0,25 | D 60 ±0,25 | D 60 ±0,25 | | 52 | 4 | - | - | - | | - | - |
| - | - | D 60,3 (2") | 53,1 | 3,6 | - | - | - | - | - | | |

Specification

- Steel **ST**
- zinc plated, blue passivated **ZB**
- Aluminium **AL**
- blank **BL**
- untreated **BL**
- anodized **EL**
- natural colour
- Stainless Steel AISI 304 **NI**
- blank **BL**
- untreated
- Sawed cross sections deburred blank, i.e. not surface treated
- Stainless Steel characteristics → Page 1144

Information

Construction tubes GN 990 can be supplied in any length up to 3000 mm. The tolerances specified for the outside diameter of the round construction tubes comply with the requirements for split mono-block connector clamps. Otherwise the tolerances comply with DIN 2391, DIN 2395 and DIN 2462. Two-piece connector clamps allow obviously larger tolerances on construction tubes.

- see also...
- Tube end plugs GN 991 → Page 1028
 - Insert bushes GN 992 → Page 1029

| How to order | 1 | Material |
|--------------|---|----------------------------------|
| 1 | 2 | d ₁ (s ₁) |
| 2 | 3 | Length l |
| 3 | 4 | Finish |

GN 990-ST-D32-460-ZB

2.1
2.2
2.3
2.4
2.5
2.6
2.7
2.8
2.9