



Type

- F with fixed handle
- D with revolving handle

Length l	s H11 Square	e min. (Column 1)	d ₁ H7 Bore	d ₂	h ₁	h ₂	h ₃ ≈	h ₄ ≈		Ø Handle
								Type D	Type E	
63	V 10	-	B 6	20	20	11	15	54,5	50	16
80	V 10	V 12	B 8	24	24	13	18	61	56	18
100	V 12	V 14	B 10	28	28	13	21	67	64	20
125	V 14	V 17	B 10	34	34	14	26	76	72	22
160	V 17	V 19	B 14	38	38	14	29	83	80	25
200	V 19	V 22	B 17	44	44	21	34	96,5	90	28
250	V 22	V 24	B 17	48	48	21	36	105,5	100	32

Specification

- Body
Cast iron (GGG)
- plastic coated
 black, textured finish
- hub machined
- Fixed handles DIN 39
Steel zinc plated, blue passivated
- Revolving handles DIN 98
Steel zinc plated, blue passivated
- Keyway P9 DIN 6885/1 → Page 1124
- Square DIN 79 → Page 1126
- Cross holes GN 110 → Page 1127
- ISO-Fundamental Tolerances → Page 1132
- RoHS-compliant

Information

The hub bores d₁ H7 are not provided for in the official standard sheet.

How to order

DIN 469-125-V17-D

1	Length l
2	s (d ₁)
3	Type