



1			2			3									
$d_1$	$d_2$		$l_1$				$d_3$	$h_1$	$h_2$	$h_3$	$h_4$ Stroke	$l_2$			
14*	M 5	M 6	12	16	20	25	32	40	50	10	25	4,5	35	3,5	45
18*	M 6	M 8	16	20	25	32	40	50	63	13,5	31	6,5	45	4	62
22*	M 10	-	20	25	32	40	50	63	80	16	36	8	52	4	74
25*	M 12	-	25	32	40	50	63	80	-	19	43	11	63	4	89
30*	M 16	-	32	40	50	63	80	-	-	23	50,5	12	76	5	108

\* \* not available from stock, requires a minimum order quantity

**Specification**

- Handle  
Zinc die casting
- plastic coated  
black, RAL 9005, textured finish ● **SW**  
orange, RAL 2004, textured finish ● **OS**
- Threaded stud and retaining screw  
Stainless Steel  
German Material No. 1.4305
- *Stainless Steel characteristics* → Page 1144
- [RoHS compliant](#)

4

**Information**

Adjustable hand levers GN 101.1 are ideal whenever parts have to be clamped in a confined space or in a particular lever position. The centre insert is connected to the lever via serrations which can easily be disengaged.

Pulling the lever disengages serrations and allowing to be swivelled to the ideal clamping position. On releasing the lever the serrations automatically re-engage.

How to order

**GN 101.1-22-M10-40-SW**

1	$d_1$
2	$d_2$
3	$l_1$
4	Colour