



- 3 Type**
- RA** Right-hand lock
 - RB** Right-hand lock, with plastic cover
 - RAK** Right-hand lock, with lock nut
 - RBK** Right-hand lock, with plastic cover, with lock nut
 - LA** Leftt-hand lock
 - LB** Leftt-hand lock, with plastic cover
 - LAK** Leftt-hand lock, with lock nut
 - LBK** Leftt-hand lock, with plastic cover, with lock nut

d₁ Pin $_{-0.02}^{-0.04}$ Bore H7	d₂	d₃	l₁	l₂	l₃ +1,5	l₄	l₅	Spring load in N \approx	
								initial	end
5*	M 10 x 1	10	37,5	6	19	21	-	7	20
6	M 12 x 1,5	12	47	8	26	26	32	8	18
8	M 16 x 1,5	16	56	10	30	32	42	11	29
10	M 20 x 1,5	20	69	12	37	37	52	21	57

* This size is only available in types LA, LAK, RA and RAK.

Specification

- Stainless Steel AISI 303
- Spring
Stainless Steel AISI 301
- Plastic cover
Technopolymer (Polyamide PA)
black, matte
- Load rating information → Page 1463
- ISO-Fundamental tolerances → Page 1479
- Stainless Steel characteristics → Page 1489
- RoHS compliant

Information

For GN 721.5 Stainless Steel-Cam action indexing plungers the indexing plunger pin is withdrawn by turning the lock by 180°. The groove on GN 721.6 cam action indexing plungers ensures that the locking pin remains in its withdrawn position.

For opposing cam action indexing plungers the left or right-handed types allow practical use, that is the same setting of the lock.

see also...

- Range of cam action indexing plungers → Page 701 ff.

How to order (without locking function)	1	d₁
	2	d₂
GN 721.5-8-M16x1,5-RAK	3	Type

How to order (with locking function)	1	d₁
	2	d₂
GN 721.6-10-M20x1,5-LBK	3	Type

3.1
3.2
3.3
3.4
3.5
3.6
3.7
3.8
3.9

