



<sup>1</sup> $l_1$	<sup>2</sup> $d_1$ Thread			<sup>2</sup> $d_2$ H7 Bore		$d_3$	$d_4$	$h_1$	$h_2$	$h_3$	$h_4$ Stroke	$t$ min.
120	M 8	M 10	M 12	B 8	B 10	16	32	29,5	2	41,5	2,5	14
145	M 12	M 16	-	B 12	B 16	23	40	42	4	56	4	22

**Specification**

- Handle  
Zinc die casting
- Plastic coated  
black, RAL 9005, textured finish **● SW**  
silver, RAL 9006, textured finish **● SR**
- Hub cover  
Plastic  
- black for SW  
- light gray for SR
- Countersunk screw  
Stainless Steel  
- chemically blackened for SW  
- blank for SR
- **GN 126**  
Threaded bushing / bore bushing  
Steel, blackened
- **GN 126.1**  
Threaded bushing / bore bushing  
Stainless Steel AISI 303
- *ISO-Fundamental tolerances* → Page 1479
- *Stainless Steel characteristics* → Page 1489
- **RoHS compliant**

**Information**

Adjustable flat tension levers GN 126 / GN 126.1 are characterized by their low height and the timelessly elegant design.

They are ideal whenever swiveling in a confined space is required or the lever is to be clamped in a particular position. The threaded insert / bored bushing is moveably attached to the handle with serrations.

Pulling the lever disengages the serrations, allowing it to be swiveled to the ideal clamping position. On “releasing” the handle, the serrations re-engage automatically.

**see also...**

- *Adjustable hand levers GN 300 (Bushing steel)* → Page 318
- *Adjustable hand levers GN 300.1 (Bushing Stainless Steel)* → Page 322
- *Adjustable Stainless Steel-Hand levers GN 300.5 (matt shot-blasted)* → Page 324
- *Adjustable flat tension levers GN 125 (Bushing, steel)* → Page 352
- *Adjustable Stainless Steel-Flat tension levers GN 125.5* → Page 354

How to order (Bushing steel)	
<sup>1</sup> $l_1$	1 $l_1$
<sup>2</sup> $d_1$ ( $d_2$ )	2 $d_1$ ( $d_2$ )
<sup>3</sup> Color	3 Color

**GN 126-120-M10-SR**

How to order (Bushing Stainless Steel)	
<sup>1</sup> $l_1$	1 $l_1$
<sup>2</sup> $d_1$ ( $d_2$ )	2 $d_1$ ( $d_2$ )
<sup>3</sup> Color	3 Color

**GN 126.1-145-M12-SW**