



Rost frei Inox
Stainless
Steel

4 Type

- A** without lock nut
- B** with lock nut

1 d_1	2 d_2	3 h_1 max.	d_3	d_4	h_2 min.	h_3 Adjustable range	h_4 min.	h_5 Adjustable range	Static load F in kN		Code no. C-Spanner	
									ST	NI		
40	79	M 10	69	M 28 x 1,5	40	53	16	59	10	100	70	DIN 1810-A40-42
40	79	M 10	86	M 28 x 1,5	40	62	24	68	18	100	70	DIN 1810-A40-42
52	99	M 12	80	M 36 x 1,5	52	61	19	69	12	125	85	DIN 1810-A52-55
52	99	M 12	103	M 36 x 1,5	52	73	30	80	23	125	85	DIN 1810-A52-55
65	119	M 16	112	M 45 x 1,5	65	82	30	90	22	225	155	DIN 1810-A65-70
65	119	M 16	148	M 45 x 1,5	65	100	48	108	40	225	155	DIN 1810-A65-70

Specification

- Steel **ST**
- zinc plated, blue passivated
- Stainless Steel AISI 304 **NI**
- *Stainless Steel characteristics* → Page 1489
- **RoHS compliant**

On request

- C-Spanner DIN 1810 (code no. see table)

Information

GN 360 levelling sets are used for leveling and to compensate for any slope when setting up machines and systems.

The thread d_2 can also be used as a through-hole for attachment from below. The fine thread d_3 laws precise adjustment and readjustment using a DIN 1810 C-Spanner. A circlip limits the maximum path of adjustment.

see also...

- *Levelling sets GN 350 / GN 350.1* → Page 850 / 851
- *Levelling sets GN 350.2 / GN 350.5* → Page 852 / 853

How to order	
1	d_1
2	d_2
3	h_1
4	Type
5	Material

GN360-119-M16-148-A-ST

