



Assembly examples




Flat hexagon nut GN 909



Mounting block GN 412.1

Application example

Positioning bushings GN 412.2 / GN 412.4



Indexing plunger / Cam action indexing plunger

Mounting blocks GN 412.1

1

2

d ₁	d ₂ +0,1 Bore	d ₃ -0,05	l ₁ -0,2	l ₂	A/F
M 12 x 1,5	B 4,2	12	10	13	13
M 12 x 1,5	B 5,2	12	10	13	13
M 12 x 1,5	B 6,2	12	10	13	13
M 16 x 1,5	B 8,2	16	12	15	17
M 16 x 1,5	B 10,2	16	12	15	17
M 16 x 1,5	B 12,2	16	12	15	17

Specification

- **GN 412.2**
Steel
 - hardened
 - blackened
- **GN 412.4**
Stainless Steel AISI 431
hardened
- *Stainless Steel characteristics* → Page 1489
- **RoHS compliant**

Information

Positioning bushings GN 412.2 / GN 412.4 are used in connection with bolts of indexing plungers and cam action indexing plungers.

The threads are adapted to the mounting blocks GN 412.1 and GN 612.1.

see also...

- *Mounting blocks GN 412.1* → Page 698
- *Mounting blocks GN 612.1* → Page 699
- *Flat hexagonal nuts GN 909* → Page 695

How to order

GN 412.2-M12x1,5-B5,2

1 d₁2 d₂

How to order

GN 412.4-M12x1,5-B5,2

1 d₁2 d₂