


Application example



1 2

m ₁	h ₁	b	d ₁	d ₂	d ₃	d ₄	h ₂	m ₂	Length l	for toggle clamps		
										GN 810 GN 810.1 GN 810.3 GN 810.4	GN 820 GN 820.1 GN 820.2 GN 820.3 GN 820.4	GN 860
82	16	19,5	6,2	M 6	9,2	12	37	22	91	130	130	125
100	18	26	8	M 8	12	16	43	27	112	230	230	200

Specification

- Steel
zinc plated, blue passivated
- RoHS

3

ST

Information

Clamping arm extenders GN 801.2 are used together with toggle clamps with "forked clamping arm" to clamp something simultaneously at two points in parallel, such as with clamping screws. These are mounted to the clamping arm and affixed in the desired position along the slot.

The side position of the clamping screws is adjusted via joints that enable any positioning of the spindle assemblies. A symmetrical arrangement/setting encourages a balanced clamping result.

All parts are supplied in a non-assembled set. Four flanged washers are included for fastening the clamping screw.

see also...

- Clamping arm extenders GN 801.1 (rigid) → New products
- Clamping arm extenders GN 809.1 → New products
- Clamping screws GN 804 → Page 585
- Clamping screws GN 807 → Page 586

How to order

GN801.2-82-16-ST

1	m ₁
2	h ₁
3	Material

