



Rostfrei Inox Stainless Steel

3 Type
A without slot
N with slot

Length $l \approx$	d_1 H9 Bore	d_2	h_1	$h_2 \approx$	$h_3 \approx$	$h_4 \approx$	$t +0,5$	\emptyset Handle	Socket cap screw DIN 912
63	B 10	18	28	18	74	40	18	18	M 5
80	B 10	18	28	18	74	40	18	18	M 5
100	B 12	20	30	20	88	50	20	21	M 6
125	B 12	20	30	20	88	50	20	21	M 6

Specification

- Stainless Steel AISI 304
 - shot-blasted
 - Crank butt-welded
- Cover cap
 - Plastic, black
- Revolving handle
 - Plastic, Duroplast black, shiny finish
 - temperature resistant up to 110 °C
- Cross holes GN 110 → Page 1422
- ISO-Fundamental tolerances → Page 1479
- Stainless Steel characteristics → Page 1489
- RoHS

Information

Stainless Steel-Cranks GN 369.5 feature a compact design and are used for light drive and positioning tasks. Thanks to the material used, the cranks are also suitable for more aggressive environments.

The slot of type N easily transfers the rotary movement to the shaft by means of a transverse pin mounted in the shaft. The crank can be connected removably or permanently fastened axially with a socket head cap screw DIN 912. Type A can be ordered with transverse holes for GN 110.

Thanks to a simple manufacturing process, it is relatively easy and inexpensive to produce these cranks as special designs.

see also...

- Cranked handles GN 670.2 (Plastic)
- Cranked handles GN 471 (Aluminum) → Page 220

How to order	1 Length l
	2 d_1
	3 Type
GN369.5-125-B12-A	

1.1
1.2
1.3
1.4
2.1
2.2
2.3
2.4